



Made by Miswa

Safety Data Sheet (SDS)

MISWA CHEMICALS - POLYGARD - ANTIFREEZE

SAFETY DATA SHEET POLYGARD BLUE ANTI-FREEZE COOLANT

SECTION 1: Identification of the substance/mixture and of the company/undertaking 1.1.

Product identifier

Product name POLYGARD BLUE ANTI-FREEZE COOLANT 16400,

Product number 16410, 16415, 16417, 16420, 16423 B16901

Internal identification

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Antifreeze liquid.

Uses advised against This product is not recommended for any industrial, professional or consumer use other than the identified uses stated above.

1.3. Details of the supplier of the safety data sheet

Supplier Miswa Chemicals Ltd
Caswell Road
Brackmills
Northampton
England
NN4 7PW
T: +44 (0)1604 701111 F:
+44 (0)1604 701120
SDSAdmin@miswa.com

1.4. Emergency telephone number Emergency

telephone Tel.: +44 (0)1604 701111 (Miswa Office Hours Monday - Friday (0900Hrs - 1700Hrs))

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (SI 2019 No. 720)


Physical hazards Not Classified

Health hazards Acute Tox. 4 - H302 STOT RE 2 - H373 Not

Environmental hazards Classified

2.2. Label elements

Hazard pictograms



Signal word Hazard Warning

statements H302 Harmful if swallowed.
H373 May cause damage to organs through prolonged or repeated exposure.



Made by Miswa

Safety Data Sheet (SDS)

MISWA CHEMICALS - POLYGARD - ANTIFREEZE

POLYGARD BLUE ANTI-FREEZE COOLANT

Precautionary statements

P260 Do not breathe vapour/ spray.
P264 Wash contaminated skin thoroughly after handling.
P270 Do not eat, drink or smoke when using this product.
P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor. P314 Get medical advice/ attention if you feel unwell.
P330 Rinse mouth.
P501 Dispose of contents/ container in accordance with national regulations. P102 Keep out of reach of children.

Contains ETHANEDIOL

2.3. Other hazards

This product does not contain any substances classified as PBT or vPvB.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

ETHANEDIOL	60-100%
CAS number: 107-21-1	EC number: 203-473-3
Classification Acute Tox. 4 - H302 STOT RE 2 - H373	
DISODIUM TETRABORATE PENTAHYDRATE	1-5%
CAS number: 12179-04-3	EC number: 215-540-4
Substance included in the Candidate List of Substances of Very High Concern according to article 59 (1,10) of regulation EC No. 1907/2006 ('REACH').	
Classification Eye Irrit. 2 - H319 Repr. 1B - H360FD	

The full text for all hazard statements is displayed in Section 16.

Composition comments The data shown are in accordance with the latest EC Directives.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information First Aid responders should pay attention to self-protection and use the recommended protective clothing (chemical resistant gloves, splash protection). If potential for exposure exists refer to Section 8 for specific personal protective equipment.

Inhalation Get medical attention. Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. When breathing is difficult, properly trained personnel may assist affected person by administering oxygen.

Ingestion Do not induce vomiting. Remove affected person from source of contamination. Get medical attention immediately.

Skin contact Remove contaminated clothing. Wash skin thoroughly with soap and water. Get medical attention if irritation persists after washing. Wash contaminated clothing before reuse.



Made by Miswa

Safety Data Sheet (SDS)

MISWA CHEMICALS - POLYGARD - ANTIFREEZE

Eye contact Flush eyes thoroughly with water for several minutes. Remove contact lenses after the initial 1-2 minutes and continue flushing for several additional minutes. If effects occur, consult a physician, preferably an ophthalmologist.

4.2. Most important symptoms and effects, both acute and delayed

General information Aside from the information found under Description of first aid measures (above) and Indication of immediate medical attention and special treatment needed (below), no additional symptoms and effects are anticipated.

4.3. Indication of any immediate medical attention and special treatment needed

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media The product is not flammable. Extinguish with alcohol-resistant foam, carbon dioxide, dry powder or water fog.

Unsuitable extinguishing media Do not use water jet as an extinguisher, as this will spread the fire.

5.2. Special hazards arising from the substance or mixture

Specific hazards Combustible Container may rupture from gas generation in a fire situation. Violent steam generation or eruption may occur upon application of direct water stream to hot liquids.

Hazardous combustion products During a fire, smoke may contain the original material in addition to combustion products of varying composition which may be toxic and/or irritating. Combustion products may include and are not limited to: Carbon monoxide. Carbon dioxide. Nitrogen oxides.

5.3. Advice for firefighters

Protective actions during firefighting Cool containers exposed to heat with water spray and remove them from the fire area if it can be done without risk. Fight advanced or massive fires from safe distance or protected location. Do not use water jet as an extinguisher, as this will spread the fire. Extinguishing waters may present a risk of damage to the environmental, collect and dispose of as hazardous waste, in accordance with local legislation.

Special protective equipment for firefighters Wear positive-pressure self-contained breathing apparatus (SCBA) and protective fire fighting clothing (includes fire fighting helmet, coat, trousers, boots, and gloves). If protective equipment is not available or not used, fight fire from a protected location or safe distance.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Isolate area. Keep unnecessary and unprotected personnel from entering the area. Refer to Section 7, Handling, for additional precautionary measures. Use appropriate safety equipment. For additional information, refer to Section 8, Exposure Controls and Personal Protection. No smoking, sparks, flames or other sources of ignition near spillage. Avoid inhalation of vapours and contact with skin and eyes.

6.2. Environmental precautions

Environmental precautions Avoid from entering into soil, ditches, sewers, waterways and/or groundwater. See Section 12, Ecological Information.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up Contain spilled material if possible. Containers with collected spillage must be properly labelled with correct contents and hazard symbol. Large spills: Dike area to contain spill. Pump into suitable and properly labeled containers. See Section 13, Disposal Considerations, for additional information.

6.4. Reference to other sections



Made by Miswa

Safety Data Sheet (SDS)

MISWA CHEMICALS - POLYGARD - ANTIFREEZE

POLYGARD BLUE ANTI-FREEZE COOLANT

Reference to other sections For personal protection, see Section 8. See Section 11 for additional information on health hazards. For waste disposal, see Section 13.

SECTION 7: Handling and storage 7.1.

Precautions for safe handling

Usage precautions Avoid spilling. Good personal hygiene procedures should be implemented. Wash hands and any other contaminated areas of the body with soap and water before leaving the work site. Avoid contact with skin and eyes.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions Store in tightly-closed, original container in a dry, cool and well-ventilated place. Keep away from food, drink and animal feeding stuffs. Keep only in the original container.

7.3. Specific end use(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.2.

SECTION 8: Exposure controls/Personal protection

8.1. Control parameters

Occupational exposure limits

ETHANEDIOL

Long-term exposure limit (8-hour TWA): WEL 52 mg/m³ 20 ppm

Short-term exposure limit (15-minute): WEL 104 mg/m³ 40 ppm vapour

Sk

Long-term exposure limit (8-hour TWA): WEL 10 mg/m³ particulate

DISODIUM TETRABORATE PENTAHYDRATE

Long-term exposure limit (8-hour TWA): 1 mg/m³

WEL = Workplace Exposure Limit.

Sk = Can be absorbed through skin.

Ingredient comments WEL = Workplace Exposure Limits

ETHANEDIOL (CAS: 107-21-1)

DNEL Industry - Dermal; Long term systemic effects: 106 mg/kg bw/day
Industry - Inhalation; Long term local effects: 35 mg/m³
Consumer - Dermal; Long term systemic effects: 53 mg/kg bw/day
Consumer - Inhalation; Long term local effects: 7 mg/m³

PNEC
- Fresh water; 10 mg/l
- marine water; 1 mg/l
- Sediment (Freshwater); 37 mg/kg sediment dw
- Intermittent release; 10 mg/l
- Soil; 1.53 mg/kg
- STP; 199.5 mg/l
- Sediment (Marinewater); 3.7 mg/kg sediment dw
- Soil; 1.53 mg/kg soil dw

DISODIUM TETRABORATE PENTAHYDRATE (CAS: 12179-04-3)

POLYGARD BLUE ANTI-FREEZE COOLANT

DNEL	Workers - Inhalation; Long term, Short term local effects, Acute: 11.7 mg/m³ Workers - Inhalation; Long term systemic effects: 6.7 mg/m³ General population - Oral; Long term, Short term systemic effects, Acute: 0.79 mg/kg bw/day General population - Inhalation; Long term, Short term local effects, Acute: 11.7 mg/m³ General population - Dermal; Long term systemic effects: 159.5 mg/kg bw/day Workers - Dermal; Long term systemic effects: 316.4 mg/kg bw/day General population - Inhalation; Long term systemic effects: 3.4 mg/m³
PNEC	- Fresh water; 2.9 mg/l - marine water; 2.9 mg/l - Intermittent release; 13.7 mg/l - STP; 10 mg/l - Soil; 5.7 mg/kg soil dw

8.2. Exposure controls

Protective equipment



Appropriate engineering controls	Provide adequate general and local exhaust ventilation. Observe any occupational exposure limits for the product or ingredients.
Eye/face protection	Use safety glasses (with side shields), consistent with EN 166 or equivalent.
Hand protection	Use chemical resistant gloves classified under Standard EN374: Protective gloves against chemicals and micro-organisms. If hands are cut or scratched, use gloves chemically resistant to this material even for brief exposures. Use gloves with insulation for thermal protection (EN 407), when needed. Examples of preferred glove barrier materials include: Butyl rubber. Natural rubber ("latex"). Neoprene. Nitrile/butadiene rubber ("nitrile" or "NBR"). Polyethylene. Ethyl vinyl alcohol laminate ("EVAL"). Polyvinyl alcohol ("PVA"). Polyvinyl chloride ("PVC" or "vinyl"). When prolonged or frequently repeated contact may occur, a glove with a protection class of 6 (breakthrough time greater than 480 minutes according to EN 374) is recommended. When only brief contact is expected, a glove with a protection class of 2 or higher (breakthrough time greater than 30 minutes according to EN 374) is recommended. NOTICE: The selection of a specific glove for a particular application and duration of use in a workplace should also take into account all relevant workplace factors such as, but not limited to: Other chemicals which may be handled, physical requirements (cut/puncture protection, dexterity, thermal protection), potential body reactions to glove materials, as well as the instructions/specifications provided by the glove supplier.
Other skin and body protection	Wear appropriate clothing to prevent any possibility of liquid contact and repeated or prolonged vapour contact.
Hygiene measures	Good personal hygiene procedures should be implemented. Wash at the end of each work shift and before eating, smoking and using the toilet. Promptly remove any clothing that becomes contaminated. Wash promptly with soap and water if skin becomes contaminated.
Respiratory protection	Respiratory protection should be worn when there is a potential to exceed the exposure limit requirements or guidelines. If there are no applicable exposure limit requirements or guidelines, wear respiratory protection when adverse effects, such as respiratory irritation or discomfort have been experienced, or where indicated by your risk assessment process. For most conditions no respiratory protection should be needed; however, if discomfort is experienced, use an approved air-purifying respirator. Use CE approved air-purifying respirator with combination filter type A1P2 minimum.
Environmental exposure controls	Do not allow material to contaminate ground water system.

SECTION 9: Physical and chemical properties



Made by Miswa

Safety Data Sheet (SDS)

MISWA CHEMICALS - POLYGARD - ANTIFREEZE

POLYGARD BLUE ANTI-FREEZE COOLANT

9.1. Information on basic physical and chemical properties

Appearance	Clear liquid.
Colour Odour	Blue.
pH	Mild. Characteristic.
Initial boiling point and range	pH (diluted solution): 7.2-8.0 @ 50% water solution
Flash point	>150°C @ 760 mm Hg
Relative density	120°C Closed cup.
Solubility(ies)	1.12-1.15 @ 20°C

9.2. Other information

Completely soluble in water.

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity

10.2. Chemical stability

Stability

Stable at normal ambient temperatures and when used as recommended.

Stable at normal ambient temperatures.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions Will not polymerise.

10.4. Conditions to avoid

Conditions to avoid Exposure to elevated temperatures can cause product to decompose. Generation of gas during decomposition can cause pressure in closed systems.

10.5. Incompatible materials

Materials to avoid Strong acids. Strong oxidising agents. Strong alkalis.

10.6. Hazardous decomposition products

Hazardous decomposition products Decomposition products depend upon temperature, air supply and the presence of other materials. Decomposition products can include and are not limited to: Aldehydes. Ethers. Alcohols.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Toxicological effects The product is not expected to be toxic to aquatic organisms.

Acute toxicity - oral

Notes (oral LD₅₀) Harmful if swallowed.

ATE oral (mg/kg)

542.75

Specific target organ toxicity - repeated exposure

STOT - repeated exposure May cause damage to organs through prolonged or repeated exposure.

General information

To the best of our knowledge the chemical, physical and toxicological properties have not been thoroughly investigated.



Made by Miswa

Safety Data Sheet (SDS)

MISWA CHEMICALS - POLYGARD - ANTIFREEZE

POLYGARD BLUE ANTI-FREEZE COOLANT

Inhalation	Unlikely to be hazardous by inhalation because of the low vapour pressure of the product at ambient temperature. Vapour may irritate respiratory system/lungs.
Ingestion	Harmful: possible risk of irreversible effects if swallowed. Headache. Nausea, vomiting. There may be soreness and redness of the mouth and throat.
Skin contact	Prolonged and frequent contact may cause redness and irritation. Not a skin sensitiser.
Eye contact	May cause eye irritation.
Acute and chronic health hazards	May cause damage to kidneys and liver through prolonged or repeated exposure (oral).
Route of exposure	Ingestion.
Medical symptoms	Headache. Nausea, vomiting.
Toxicological information on ingredients.	

ETHANEDIOL

Acute toxicity - oral Acute

toxicity oral (LD₅₀ 7,712.0

mg/kg)

Species

Rat

Notes (oral LD₅₀)

Acute oral toxicity is expected to be moderate in humans even though animals test results would suggest a low toxicity. Ingestion of approximately 100ml has caused death in humans. Ingestion may cause nausea, vomiting, abdominal discomfort or diarrhea. Excessive exposure may cause central nervous system effects, cardiopulmonary effects and kidney failure.

ATE oral (mg/kg) 500.0

Acute toxicity - dermal

Acute toxicity dermal (LD₅₀ 3,501.0

mg/kg)

Species

Mouse

ATE dermal (mg/kg) 3,501.0

Acute toxicity - inhalation

Acute toxicity inhalation (LC₅₀

vapours mg/l)

Species

2.6

Notes (inhalation LC₅₀)

Rat

At room temperature exposure to vapour is minimal due to low volatility. With good ventilation single exposure is not expected to cause adverse effect. If the product is heated or the working area has poor ventilation, vapour/mist may accumulate and cause respiratory irritation and symptoms such as headache and nausea.

Skin corrosion/irritation Animal

data Not irritating. Rabbit

Serious eye damage/irritation

Serious eye damage/irritation Not irritating. Rabbit

Respiratory sensitisation

Miswa Chemicals Ltd

53-54 Caswell Road, Brackmills Industrial Estate, Northampton, NN4 7PW

Tel: (0)1604 701111 - www.miswa.com





Made by Miswa

Safety Data Sheet (SDS)

MISWA CHEMICALS - POLYGARD - ANTIFREEZE

POLYGARD BLUE ANTI-FREEZE COOLANT

Respiratory sensitisation	Guinea pig: Not sensitising.
Skin sensitisation	
Skin sensitisation	- Guinea pig: Not sensitising.
Germ cell mutagenicity	
Genotoxicity - in vitro	Negative.
Genotoxicity - in vivo	Negative.
Carcinogenicity	
Carcinogenicity	The current toxicological knowledge allows to not classify the product as a carcinogen.
Reproductive toxicity	
Reproductive toxicity - fertility	Ingestion of large amounts has been shown to interfere with reproduction in animals.
Specific target organ toxicity - repeated exposure	
STOT - repeated exposure	Observations in humans include: Nystagmus (involuntary eye movement). In animals effects have been reported on the following organs: kidneys and liver. NOAEL 150 mg/kg/day, Oral, Rat
Target organs	Kidneys
Inhalation	At room temperature, exposure to vapor is minimal due to low volatility. With good ventilation, single exposure is not expected to cause adverse effects. If material is heated or areas are poorly ventilated, vapor/mist may accumulate and cause respiratory irritation and symptoms such as headache and nausea.
Ingestion	Oral toxicity is expected to be moderate in humans due to ethylene glycol even though tests with animals show a lower degree of toxicity. Ingestion of quantities (approximately 65 mL (2 oz.) for diethylene glycol or 100 mL (3 oz.) for ethylene glycol) has caused death in humans. May cause nausea and vomiting. May cause abdominal discomfort or diarrhea. Excessive exposure may cause central nervous system effects, cardiopulmonary effects (metabolic acidosis), and kidney failure. For Ethylene glycol: Lethal Dose, Human, adult 100 ml LD50, rat, male and female 7,712 mg/kg.
Skin contact	Prolonged skin contact is unlikely to result in absorption of harmful amounts. Repeated skin exposure to large quantities may result in absorption of harmful amounts. Massive contact with damaged skin or of material sufficiently hot to burn skin may result in absorption of potentially lethal amounts.
Eye contact	May cause temporary eye irritation.
Route of exposure	Ingestion.
Target organs	Kidneys Liver

DISODIUM TETRABORATE PENTAHYDRATE

Acute toxicity - oral Acute	
toxicity oral (LD ₅₀ mg/kg)	3,305.0
Species	Rat
Notes (oral LD ₅₀)	Low acute oral toxicity.



Made by Miswa

Safety Data Sheet (SDS)

MISWA CHEMICALS - POLYGARD - ANTIFREEZE

POLYGARD BLUE ANTI-FREEZE COOLANT

ATE oral (mg/kg)	3,305.0
Acute toxicity - dermal	
Acute toxicity dermal (LD ₅₀ mg/kg)	2,001.0
Species	Rabbit
Notes (dermal LD ₅₀)	The substance is poorly absorbed through intact skin. Low acute dermal toxicity.
ATE dermal (mg/kg)	2,001.0
Acute toxicity - inhalation	
Notes (inhalation LC ₅₀)	Low acute inhalation toxicity.
Skin corrosion/irritation	
Animal data	Not irritating.
Serious eye damage/irritation	
Serious eye damage/irritation	Moderately irritating.
Respiratory sensitisation	
Respiratory sensitisation	Data lacking.
Skin sensitisation	
Skin sensitisation	Not sensitising.
Carcinogenicity	
Carcinogenicity	No evidence of carcinogenicity in animal studies.
Reproductive toxicity	
Reproductive toxicity - fertility	Known reproductive toxicant based on animal evidence.
Reproductive toxicity - development	Known reproductive toxicant based on animal evidence.
Specific target organ toxicity - single exposure	
STOT - single exposure	Conclusive data but not sufficient for classification.
Specific target organ toxicity - repeated exposure	
STOT - repeated exposure	Conclusive data but not sufficient for classification.
Aspiration hazard	
Aspiration hazard	Conclusive data but not sufficient for classification.
Skin contact	Not irritating. Not a skin sensitiser.
Eye contact	Mild eye irritant in rabbits.

SECTION 12: Ecological information

Ecotoxicity	The product is not expected to be hazardous to the environment. The product components are not classified as environmentally hazardous. However, large or frequent spills may have hazardous effects on the environment.
-------------	--



Made by Miswa

Safety Data Sheet (SDS)

MISWA CHEMICALS - POLYGARD - ANTIFREEZE

POLYGARD BLUE ANTI-FREEZE COOLANT

Ecological information on ingredients.

DISODIUM TETRABORATE PENTAHYDRATE

Ecotoxicity

Boron occurs naturally in sea water at an average concentration of 5 mg B/l and fresh water at 1 mg B/l or less. In dilute aqueous solutions the predominant boron species present is undissociated boric acid.

12.1. Toxicity

Toxicity

The product is not expected to be toxic to aquatic organisms.

Ecological information on ingredients.

ETHANEDIOL

Toxicity

Product not classified as dangerous to aquatic organisms.

Acute aquatic toxicity

Acute toxicity - fish

LC₅₀, 96 hours: 72860 mg/l, Pimephales promelas (Fat-head Minnow) EC₅₀,

48 hours: > 100 mg/l, Daphnia magna

Acute toxicity - aquatic invertebrates

EC₅₀, 96 hours: 6500 - 13000 mg/l, Selenastrum capricornutum EC₂₀,

Acute toxicity - aquatic plants

30 minutes: > 1995 mg/l, Activated sludge

Acute toxicity - microorganisms

Chronic aquatic toxicity

NOEC, 7 days: 15380 mg/l, Pimephales promelas (Fat-head Minnow)

Chronic toxicity - fish early life stage

NOEC, 7 days: 8590 mg/l, Ceriodaphnia Sp.

Chronic toxicity - aquatic invertebrates

DISODIUM TETRABORATE PENTAHYDRATE

Toxicity

All toxicity values relate to Boron (Boron = Disodium Tetraborate Pentahydrate multiplied by 0.1484).

Acute aquatic toxicity

Acute toxicity - fish

LC₅₀, 96 hours: 79.7 mg B/L, Pimephales promelas (Fat-head Minnow) LC₅₀,

Acute toxicity - aquatic invertebrates

48 hours: 133 mg B/L, Daphnia magna

Acute toxicity - aquatic plants

EC₅₀, 72 hours: 40 mg B/L, Selenastrum capricornutum

Chronic aquatic toxicity

Toxicity to terrestrial plants

Boron is an essential micronutrient for healthy growth of plants, however, it can be harmful to boron sensitive plants in higher quantities. Care should be taken to minimise the amount of borate product released to the environment.

12.2. Persistence and degradability

Persistence and degradability

The product is biodegradable but it must not be discharged into drains without permission from the authorities. The product is degraded completely by photochemical oxidation.

Ecological information on ingredients.

Miswa Chemicals Ltd

53-54 Caswell Road, Brackmills Industrial Estate, Northampton, NN4 7PW
Tel: (0)1604 701111 - www.miswa.com





Made by Miswa

Safety Data Sheet (SDS)

MISWA CHEMICALS - POLYGARD - ANTIFREEZE

POLYGARD BLUE ANTI-FREEZE COOLANT

ETHANEDIOL

Persistence and degradability	The product is biodegradable.
Biodegradation	Water - Degradation (%) 90 - 100%: 10 days Passes OECD test(s) for ready biodegradability. Material is ultimately biodegradable (reaches > 70% biodegradation in OECD test(s) for inherent biodegradability).

DISODIUM TETRABORATE PENTAHYDRATE

Persistence and degradability	Boron is naturally occurring and ubiquitous in the environment. Borax pentahydrate decomposes in the environment to natural borate.
-------------------------------	---

12.3. Bioaccumulative potential

Bioaccumulative potential	The product does not contain any substances expected to be bioaccumulating.
---------------------------	---

Ecological information on ingredients.

ETHANEDIOL

Bioaccumulative potential	Not potentially bioaccumulative
Partition coefficient	log Pow: -1.36

DISODIUM TETRABORATE PENTAHYDRATE

Bioaccumulative potential	The product is not bioaccumulating.
---------------------------	-------------------------------------

12.4. Mobility in soil

Mobility	The product is soluble in water. Volatilization from natural bodies of water or moist soil is not expected to be an important fate process.
----------	---

Ecological information on ingredients.

ETHANEDIOL

Mobility	The product is soluble in water. Volatilization from natural bodies of water or moist soil is not expected to be an important fate process. Potential for mobility in soil is very high.
Adsorption/desorption coefficient	Water - Koc: ~ 1 @ °C
Henry's law constant	~ 8.05E-09 atm m ³ /mol @ 25°C

DISODIUM TETRABORATE PENTAHYDRATE

Mobility	The product is soluble in water. Potential for mobility in soil is very high.
----------	---

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB assessment	This product does not contain any substances classified as PBT or vPvB.
------------------------------------	---

Ecological information on ingredients.

ETHANEDIOL



Made by Miswa

Safety Data Sheet (SDS)

MISWA CHEMICALS - POLYGARD - ANTIFREEZE

POLYGARD BLUE ANTI-FREEZE COOLANT

Results of PBT and vPvB
assessment

This substance is not classified as PBT or vPvB according to current UK criteria.

DISODIUM TETRABORATE PENTAHYDRATE

Results of PBT and vPvB
assessment

PBT assessment does not apply.

12.6. Other adverse effects

Other adverse effects Not applicable.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

General information

This product, when being disposed of in its unused and uncontaminated state should be treated as a hazardous waste according to EC Directive 2008/98/EC. Any disposal practices must be in compliance with all national and provincial laws and any municipal or local by-laws governing hazardous waste. For used, contaminated and residual materials additional evaluations may be required.

Disposal methods

Residues and empty containers should be taken care of as hazardous waste according to local and national provisions. Avoid the spillage or runoff entering drains, sewers or watercourses.

SECTION 14: Transport information

General

The product is not covered by international regulations on the transport of dangerous goods (IMDG, IATA, ADR/RID).

14.1. UN number

Not applicable.

14.2. UN proper shipping name

Not applicable.

14.3. Transport hazard class(es)

No transport warning sign required.

14.4. Packing group

Not applicable.

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant
No.

14.6. Special precautions for user

Not applicable.

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to
Annex II of MARPOL 73/78 and
the IBC Code

Not applicable.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Miswa Chemicals Ltd

53-54 Caswell Road, Brackmills Industrial Estate, Northampton, NN4 7PW
Tel: (0)1604 701111 - www.miswa.com





Made by Miswa

Safety Data Sheet (SDS)

MISWA CHEMICALS - POLYGARD - ANTIFREEZE

POLYGARD BLUE ANTI-FREEZE COOLANT

National regulations Control of Pollution (Special Waste) Regulations 1980 (as amended).
The Chemicals (Health and Safety) and Genetically Modified Organisms (Contained Use) (Amendment etc.) (EU Exit) Regulations 2019, SI 2019 No. 720 (as amended)
The REACH etc. (Amendment etc.) (EU Exit) Regulations 2019, SI 2019 No. 758 (as amended)

Guidance Workplace Exposure Limits EH40.
Introduction to Local Exhaust Ventilation HS(G)37.

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

SECTION 16: Other information

Revision comments Issued	NOTE: Lines within the margin indicate significant changes from the previous revision.
by	HS&E Manager.
Revision date	14/07/2023
Revision	10
Supersedes date	17/09/2021
SDS status	Approved.
Hazard statements in full	H302 Harmful if swallowed. H319 Causes serious eye irritation. H360FD May damage fertility if swallowed. May damage the unborn child if swallowed. H373 May cause damage to organs through prolonged or repeated exposure. H373 May cause damage to organs (Kidneys) through prolonged or repeated exposure if swallowed.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.